



Higgins Slurry Emulsion is a polymer modified, cationic quick set (CQS) emulsion specifically designed for use in slurry and microsurfacing applications.

Formulated to optimise mixing time whilst building cohesion quickly Higgins Slurry Emulsion is ideal for the design and construction of high performance slurry and microsurfacing systems.

➤ WHERE TO USE

- High performance slurry and microsurfacing systems.
- Tack coat
- Aggregate Precoating
- Enrichment and Fog Seals.

➤ TYPICAL PROPERTIES OF SLURRY EMULSION

Residual Binder Type		Polymer Modified Bitumen
Binder Content	In-House Method NTM 02	65%
Brookfield Viscosity (25°C)	ASTM D2196	100 mPa.s
Sieve Residue (150µm)	AS2341.26	0.1%

➤ APPLICATION AND DESIGN

Storage Life	Up to 60 Days
Storage Temperature	10 - 50°C
Application Temperature	20 - 40°C
Air and Pavement Temperature	10°C and rising
<ul style="list-style-type: none">• Slurry emulsion can be used for designs based on NZTA, Austroads, ISSA or ASTM procedures.• Consult the manufacturer if further guidance is required.• A Safety Data Sheet (SDS) is available upon request.	

For more information on the availability of Slurry Emulsion please contact:
Higgins Bitumen (a division of Higgins Contractors Ltd),
PO Box 421, Napier
P: (06) 834-1589 E: HBM@higgins.co.nz

October 2014
Version 3

To the best of our knowledge the information contained in this document is correct. Since the products described herein are being continuously improved, the specified properties may vary as improvements are made to production processes and product quality. This document may be revised at any time.